



Item # 20484433, EXTREMEFLEX ARCTIC Petroleum Transfer Hose 2 in x 100 ft, 150 psi, Blue

APPLICATION: An extremely flexible and lightweight drop hose for transfer of petroleum-based products under suction, low-pressure discharge or gravity flow. Flexibility maintained down to -65 °F (-54 °C).

CONSTRUCTION TUBE: Black Nitrile, RMA Class A (High Oil Resistance)

COVER:

Corrugated Black Wingprene® synthetic rubber (wrapped impression), blue spiral stripe

Corrugated Blue Wingprene® synthetic rubber (wrapped impression), red spiral stripe

REINFORCEMENT: Spiral-plied synthetic fabric with double wire helix

TEMPERATURE: -65 °F to 180 °F (-54 °C to 82 °C)

COUPLINGS: Use Continental Contitech Insta-Lock™ Cam & Groove Fittings

BRANDING (SPIRAL): Example: Continental Contitech Plicord® Arctic ExtremeFlex™ Petroleum Transfer 150 psi WP



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Petroleum Transfer
Style	Petrol Transfer Hose
Construction Tube	Black Nitrile, RMA Class A (High Oil Resistance)
Cover	Corrugated Blue Wingprene® synthetic rubber (wrapped impression), red spiral stripe
Reinforcement	Spiral-plied synthetic fabric with double wire helix

Color	Blue
Min. Temperature	-65 °F -54 °C
Max. Temperature	180 °F 82 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Brand	ARCTIC EXTREMEFLEX™
Order Code	543-451

Specifications

I.D.	2 in 51.00 mm
Nom. O.D.	2.500 in 63.50 mm
Length	100.000 ft
Bend Radius	2.000 in 51.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	1.080 lb/ft 1.61 kg/m

MidEastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech