



## Item # 20459046, EXTREMEFLEX PETROLEUM Transfer Hose 2 1/2 in x 100 ft, 200 psi, Black

**APPLICATION:** An extremely flexible and lightweight drop hose for use in tank truck and in-plant operation to transfer diesel, ethanol, gasoline, oil and petroleum base products up to 60% aromatic content. Corrugated construction for lower drag coefficient and superior abrasion resistance.

**CONSTRUCTION TUBE:** Black Nitrile synthetic rubber (Class A oil resistance)

**COVER:** Black Chemivic™ synthetic (corrugated)

**REINFORCEMENT:** Spiral plied synthetic fabric with wire helix

**TEMPERATURE:** -40 °F to 200 °F (-40 °C to 93 °C)

**COUPLINGS:** Use Continental Contitech Insta-Lock™ Cam & Groove Fittings.

**BRANDING (SPIRAL):** Example: Plicord® ExtremeFlex™ Petroleum Transfer



[Product Specifications](#) | [Specifications](#)

### Product Specifications

<b>Type</b>	Petroleum Transfer
<b>Style</b>	Petrol Transfer Hose
<b>Construction Tube</b>	Black Nitrile synthetic rubber (Class A oil resistance)
<b>Cover</b>	Black Chemivic™ synthetic (corrugated)
<b>Reinforcement</b>	Spiral plied synthetic fabric with wire helix
<b>Color</b>	Black

<b>Min. Temperature</b>	-40 °F -40 °C
<b>Max. Temperature</b>	200 °F 93 °C
<b>Max. Working Pressure</b>	200.0 psi 1.37 MPa
<b>Brand</b>	PLICORD® EXTREMEFLEX™
<b>Order Code</b>	543-216

### Specifications

<b>I.D.</b>	2 1/2 in 63.00 mm
<b>Nom. O.D.</b>	3.000 in 76.10 mm
<b>Length</b>	100.000 ft
<b>Bend Radius</b>	2.500 in 63.50 mm
<b>Vacuum Rating</b>	29.000 inHg 737.00 mmHg
<b>Weight</b>	1.410 lb/ft 2.10 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)  
1-800-235-4632  
Contitech.us

**ContiTech**