



## Item # 20017598, FLEXTRA 100 RED Petroleum Transfer Hose 3 in x 100 ft, 100 psi, Red

**APPLICATION:** A high quality wand hose used in asphalt crack filling applicator and dispensing service.

**CONSTRUCTION TUBE:** Black Nitrile (special heat resistance)

**COVER:** Black Wingprene® (wrapped finish) flame-retardant

**REINFORCEMENT:** Spiral-plied (2) steel wire

**TEMPERATURE:** -25 °F to 350 °F (-32 °C to 177 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING (SPIRAL):** Example: Continental Contitech Pyroflex Hot Tar Wand Hose.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

Type	Petrol Transfer
Style	Petrol Transfer Hose
Construction Tube	Nitrile synthetic rubber RMA Class A (High Oil Resistance)
Cover	Red Wingprene®, corrugated synthetic rubber RMA Class A (High Oil Resistance).
Reinforcement	Spiral-plied synthetic fabric with double wire helix
Color	Red
Min. Temperature	-30 °F -34 °C

<b>Max. Temperature</b>	180 °F 82 °C
<b>Max. Working Pressure</b>	100.0 psi 0.69 MPa
<b>Brand</b>	RED FLEXTRA®
<b>Order Code</b>	543-123

### Specifications

<b>I.D.</b>	3 in 76.20 mm
<b>Nom. O.D.</b>	3.410 in 86.60 mm
<b>Total Width</b>	3.410 in 86.60 mm
<b>Length</b>	100.000 ft
<b>Bend Radius</b>	6.000 in 152.00 mm
<b>Vacuum Rating</b>	29.000 inHg 737.00 mmHg
<b>Weight</b>	1.410 lb/ft 2.10 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)  
1-800-235-4632  
Contitech.us

**ContiTech**