



Item # 20459048, EXTREMEFLEX PETROLEUM Transfer Hose 4 in x 100 ft, 150 psi, Black

APPLICATION: An extremely flexible and lightweight drop hose for use in tank truck and in-plant operation to transfer diesel, ethanol, gasoline, oil and petroleum base products up to 60% aromatic content. Corrugated construction for lower drag coefficient and superior abrasion resistance.

CONSTRUCTION TUBE: Black Nitrile synthetic rubber (Class A oil resistance)

COVER: Black Chemivic™ synthetic (corrugated)

REINFORCEMENT: Spiral plied synthetic fabric with wire helix

TEMPERATURE: -40 °F to 200 °F (-40 °C to 93 °C)

COUPLINGS: Use Continental Contitech Insta-Lock™ Cam & Groove Fittings.

BRANDING (SPIRAL): Example: Plicord® ExtremeFlex™ Petroleum Transfer



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Petroleum Transfer
Style	Petrol Transfer Hose
Construction Tube	Black Nitrile synthetic rubber (Class A oil resistance)
Cover	Black Chemivic™ synthetic (corrugated)
Reinforcement	Spiral plied synthetic fabric with wire helix
Color	Black

Min. Temperature	-40 °F -40 °C
Max. Temperature	200 °F 93 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Brand	PLICORD® EXTREMEFLEX™
Order Code	543-216

Specifications

I.D.	4 in 102.00 mm
Nom. O.D.	4.560 in 115.70 mm
Length	100.000 ft
Bend Radius	4.000 in 101.60 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	2.420 lb/ft 3.61 kg/m

MideastUS@contitech.us
1-800-235-4632
Contitech.us

ContiTech