



Item # 20484436, EXTREMEFLEX ARCTIC Petroleum Transfer Hose 4 in x 100 ft, 150 PSI, Blue

APPLICATION: An extremely flexible and lightweight drop hose for transfer of petroleum-based products under suction, low-pressure discharge or gravity flow. Flexibility maintained down to -65 °F (-54 °C).

CONSTRUCTION TUBE: Black Nitrile, RMA Class A (High Oil Resistance)

COVER:

Corrugated Black Wingprene® synthetic rubber (wrapped impression), blue spiral stripe

Corrugated Blue Wingprene® synthetic rubber (wrapped impression), red spiral stripe

REINFORCEMENT: Spiral-plied synthetic fabric with double wire helix

TEMPERATURE: -65 °F to 180 °F (-54 °C to 82 °C)

COUPLINGS: Use Continental Contitech Insta-Lock™ Cam & Groove Fittings

BRANDING (SPIRAL): Example: Continental Contitech Plicord® Arctic ExtremeFlex™ Petroleum Transfer 150 psi WP



[Product Specifications](#) | [Specifications](#)

Product Specifications

| | |
|--------------------------|---|
| Type | Petroleum Transfer |
| Style | Petrol Transfer Hose |
| Construction Tube | Black Nitrile, RMA Class A (High Oil Resistance) |
| Cover | Corrugated Blue Wingprene® synthetic rubber (wrapped impression), red spiral stripe |
| Reinforcement | Spiral-plied synthetic fabric with double wire helix |

| | |
|------------------------------|-----------------------|
| Color | Blue |
| Min. Temperature | -65 °F -54 °C |
| Max. Temperature | 180 °F 82 °C |
| Max. Working Pressure | 150.0 psi 1.03 MPa |
| Brand | ARCTIC EXTREMEFLEX™ |
| Order Code | 543-451 |

Specifications

| | |
|----------------------|----------------------------|
| I.D. | 4 in 102.00 mm |
| Nom. O.D. | 4.550 in 115.70 mm |
| Length | 100.000 ft |
| Bend Radius | 4.000 in 102.00 mm |
| Vacuum Rating | 29.000 inHg 737.00 mmHg |
| Weight | 2.350 lb/ft 3.50 kg/m |

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech