



™

Kuriyama of America, Inc.

360 E. State Parkway
Schaumburg, IL 60173-5335 USA

Phone: (847) 755-0360

Toll-Free FAX: (800) 800-0320

International FAX: (847) 885-0996 **Email:** sales@kuriyama.com

Series Number WOR300X100, WOR™ Series 3 in. ID Heavy Duty Oil Resistant PVC Suction Hose

Made in the USA



[General Applications](#) | [Construction](#) | [Service Temperature](#) | [Features and Advantages](#) | [Nominal Specifications](#) | [Specifications](#) | [Note](#) | [Compliance Footnotes](#)

General Applications -**General Applications**

- Environmental clean-up
- Oil skimming
- Oil slurries
- Oil suction
- Vapor recovery - hydrocarbon emissions

Construction -**Construction**

Oil resistant PVC tube with rigid PVC helix.

Service Temperature -**Service Temperature [Min]**

-15 °C
5 °F

Service Temperature [Max]

65 °C
150 °F

Features and Advantages

Features and Advantages

- **Oil Resistant PVC Tube** - Made with special oil resistant compounds which exhibit medium resistance to oil and other hydrocarbons.
- **Convuluted Outer Cover** - Provides increased hose flexibility.
- **Phthalate Free**

Nominal Specifications

ID	3 in 76.2 mm
OD	3.64 in 92.5 mm
Working Pressure at 68°F	40 psi
Working Pressure at 104°F	20 psi
Vacuum Rating at 68°F	28 inHg
Vacuum Rating at 104°F	24 inHg
Min. Bending Radius at 68°F	6 in
Standard Length	100 ft
Weight	1.17 lbs/ft

Specifications

Brand	Tigerflex®
Series	WOR300
Type	Heavy Duty Oil Resistant PVC Suction Hose
Material	PVC
Color	Orange
Performance	Vapor Recovery - Hydrocarbon Emissions

Note

Note

Service life may vary depending on operating conditions and type of material being conveyed.

Compliance Footnotes

Compliance Footnotes

Phthalate Free - Manufactured from all phthalate free materials.

RoHS - The product complies with the requirements of the EU directive 2002/95/EC which is on the restriction of the use of certain hazardous substances in electrical and electronic equipment.