



CHEM ONE™ Chemical Transfer Hose



APPLICATION: For the transfer of a variety of current industrial chemicals used today. (Refer to Continental Contitech Chemical Resistance Guide for compatibility.) For use in pressure, gravity flow and/or suction service.

CONSTRUCTION TUBE: Alphasyn® Modified Cross-Linked Polyethylene (Mod XLPE).

COVER: Black corrugated abrasion-resistant Omegasyn™ EPDM with Red Spiral Stripe

REINFORCEMENT: Spiral plied synthetic fabric with double wire helix

TEMPERATURE: -40 °F to 250 °F (-40 °C to 121 °C)

COUPLINGS: Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product.

BRANDING: Example: CHEM ONE™ chemical transfer hose Alphasyn® 200 PSI WP Continental Contitech

1

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Total Width</u>	<u>Length</u>	<u>Bend Radius</u>	<u>Weight</u>
20408836	3/4 in 19.00 mm	1.200 in 30.50 mm	1.200 in 30.50 mm	400.000 ft	2.000 in 50.80 mm	0.390 lb/ft 0.58 kg/m
20408837	1 in 25.30 mm	1.400 in 36.80 mm	1.400 in 36.80 mm	100.000 ft	3.000 in 76.20 mm	0.490 lb/ft 0.73 kg/m
20413575	1 in 25.30 mm	1.400 in 36.80 mm	1.400 in 36.80 mm	4.000 ft	3.000 in 76.20 mm	0.490 lb/ft 0.73 kg/m
20540455	1 in 25.30 mm	1.400 in 36.80 mm	1.400 in 36.80 mm	250.000 ft	3.000 in 76.20 mm	0.490 lb/ft 0.73 kg/m
20408838	1 1/4 in 32.00 mm	1.600 in 42.20 mm	1.600 in 42.20 mm	100.000 ft	3.000 in 76.20 mm	0.530 lb/ft 0.78 kg/m

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Total Width</u>	<u>Length</u>	<u>Bend Radius</u>	<u>Weight</u>
20408870	1 1/2 in 38.00 mm	1.900 in 48.30 mm	1.900 in 48.3 mm	100.000 ft	4.000 in 101.60 mm	0.630 lb/ft 0.93 kg/m
20483536	1 1/2 in 38.00 mm	1.900 in 48.30 mm	1.900 in 48.3 mm	3.000 ft	4.000 in 101.60 mm	0.630 lb/ft 0.93 kg/m
20408871	2 in 51.00 mm	2.400 in 61.80 mm	2.400 in 61.80 mm	100.000 ft	5.000 in 127.00 mm	0.860 lb/ft 1.28 kg/m
20409794	2 in 51.00 mm	2.400 in 61.80 mm	2.400 in 61.80 mm	400.000 ft	5.000 in 127.00 mm	0.860 lb/ft 1.28 kg/m
20409795	2 in 51.00 mm	2.400 in 61.80 mm	2.400 in 61.80 mm	15.000 ft	5.000 in 127.00 mm	0.860 lb/ft 1.28 kg/m
20410466	2 in 51.00 mm	2.400 in 61.80 mm	2.400 in 61.80 mm	3.000 ft	5.000 in 127.00 mm	0.860 lb/ft 1.28 kg/m
20410846	2 in 51.00 mm	2.400 in 61.80 mm	2.400 in 61.80 mm	6.000 ft	5.000 in 127.00 mm	0.860 lb/ft 1.28 kg/m
20410885	2 in 51.00 mm	2.400 in 61.80 mm	2.400 in 61.80 mm	20.000 ft	5.000 in 127.00 mm	0.860 lb/ft 1.28 kg/m
20410888	2 in 51.00 mm	2.400 in 61.80 mm	2.400 in 61.80 mm	5.000 ft	5.000 in 127.00 mm	0.860 lb/ft 1.28 kg/m
20410889	2 in 51.00 mm	2.400 in 61.80 mm	2.400 in 61.80 mm	2.000 ft	5.000 in 127.00 mm	0.860 lb/ft 1.28 kg/m
20427662	2 in 51.00 mm	2.400 in 61.80 mm	2.400 in 61.80 mm	4.000 ft	5.000 in 127.00 mm	0.860 lb/ft 1.28 kg/m
20432797	2 in 51.00 mm	2.400 in 61.80 mm	2.400 in 61.80 mm	10.000 ft	5.000 in 127.00 mm	0.860 lb/ft 1.28 kg/m
20525682	2 in 51.00 mm	2.400 in 61.80 mm	2.400 in 61.80 mm	25.000 ft	5.000 in 127.00 mm	0.860 lb/ft 1.28 kg/m
20408872	2 1/2 in 63.00 mm	2.900 in 75.60 mm	2.900 in 75.60 mm	100.000 ft	6.000 in 152.40 mm	1.240 lb/ft 1.84 kg/m
20408873	3 in 76.00 mm	3.400 in 88.10 mm	3.400 in 88.10 mm	100.000 ft	8.000 in 203.20 mm	1.460 lb/ft 2.17 kg/m
20451016	3 in 76.00 mm	3.400 in 88.10 mm	3.400 in 88.10 mm	20.000 ft	8.000 in 203.20 mm	1.460 lb/ft 2.17 kg/m

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Total Width</u>	<u>Length</u>	<u>Bend Radius</u>	<u>Weight</u>
20451235	3 in 76.00 mm	3.400 in 88.10 mm	3.400 in 88.10 mm	4.000 ft	8.000 in 203.20 mm	1.460 lb/ft 2.17 kg/m
20462713	4 in 102.00 mm	4.500 in 115.00 mm	4.500 in 115.0 mm	400.000 ft	11.000 in 279.40 mm	2.060 lb/ft 3.06 kg/m
20476492	3/4 in 19.00 mm	1.200 in 30.50 mm	1.200 in 30.50 mm	5.000 ft	2.000 in 50.80 mm	0.390 lb/ft 0.58 kg/m

MideastUS@contitech.us
1-800-235-4632
Contitech.us

ContiTech