



## FRONTIER® 200 Multipurpose Hose



**APPLICATION:** An economical air and water hose, FRONTIER® is for a wide range of industrial, construction and agricultural applications. Available in 200, 250, and 300 psi working pressures.

**CONSTRUCTION TUBE:** EPDM(compound)® synthetic rubber, RMA Class C (Limited Oil Resistance)

**COVER:** Black, Red, Yellow, Green or Blue EPDM(compound)® synthetic rubber

**REINFORCEMENT:** Spiral synthetic yarn, 2" is braided

**TEMPERATURE:** -40 °F to 190 °F (-40 °C to 88 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING:** Example: 1/2" FRONTIER® Continental Contitech 200 psi WP.

1

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Color</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
<a href="#">20025631</a>	3/4 in 19.10 mm	1.120 in 28.50 mm	50.000 ft	Black	200.0 psi 1.38 MPa	0.340 lb/ft 0.51 kg/m
<a href="#">20316536</a>	5/8 in 15.90 mm	0.970 in 24.60 mm	300.000 ft	Black	200.0 psi 1.38 MPa	0.270 lb/ft 0.40 kg/m
<a href="#">20334065</a>	5/8 in 15.90 mm	0.970 in 24.60 mm	700.000 ft	Black	200.0 psi 1.38 MPa	0.270 lb/ft 0.40 kg/m
<a href="#">20414668</a>	5/8 in 15.90 mm	0.970 in 24.60 mm	328.000 ft	Black	200.0 psi 1.38 MPa	0.270 lb/ft 0.40 kg/m
<a href="#">20467894</a>	3/8 in 9.50 mm	0.670 in 17.00 mm	250.000 ft	Black	200.0 psi 1.38 MPa	0.150 lb/ft 0.22 kg/m
<a href="#">20529986</a>	3/8 in 9.50 mm	0.670 in 17.00 mm	250.000 ft	Black	200.0 psi 1.38 MPa	0.150 lb/ft 0.22 kg/m

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Color</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
<a href="#">20321354</a>	3/8 in 9.50 mm	0.670 in 17.00 mm	250.000 ft	Black	200.0 psi 1.38 MPa	0.150 lb/ft 0.22 kg/m
<a href="#">20022883</a>	1 1/4 in 31.80 mm	2.730 in 44.00 mm	400.000 ft	Black	200.0 psi 1.38 MPa	0.750 lb/ft 1.12 kg/m
<a href="#">20022884</a>	1 1/4 in 31.80 mm	2.730 in 44.00 mm	300.000 ft	Black	200.0 psi 1.38 MPa	0.750 lb/ft 1.12 kg/m
<a href="#">20022890</a>	1 1/2 in 38.10 mm	1.980 in 50.30 mm	300.000 ft	Black	200.0 psi 1.38 MPa	0.860 lb/ft 1.28 kg/m
<a href="#">20022891</a>	1 1/2 in 38.10 mm	1.980 in 50.30 mm	300.000 ft	Black	200.0 psi 1.38 MPa	0.860 lb/ft 1.28 kg/m
<a href="#">20022897</a>	2 in 50.80 mm	2.500 in 63.50 mm	200.000 ft	Black	200.0 psi 1.38 MPa	1.160 lb/ft 1.73 kg/m
<a href="#">20288283</a>	2 in 50.80 mm	2.500 in 63.50 mm	110.000 ft	Black	200.0 psi 1.38 MPa	1.160 lb/ft 1.73 kg/m
<a href="#">20022916</a>	1 1/4 in 31.80 mm	2.730 in 44.00 mm	400.000 ft	Red	200.0 psi 1.38 MPa	0.750 lb/ft 1.12 kg/m
<a href="#">20022917</a>	1 1/4 in 31.80 mm	2.730 in 44.00 mm	300.000 ft	Red	200.0 psi 1.38 MPa	0.750 lb/ft 1.12 kg/m
<a href="#">20022926</a>	1 1/2 in 38.10 mm	1.980 in 50.30 mm	300.000 ft	Red	200.0 psi 1.38 MPa	0.860 lb/ft 1.28 kg/m
<a href="#">20022927</a>	1 1/2 in 38.10 mm	1.980 in 50.30 mm	300.000 ft	Red	200.0 psi 1.38 MPa	0.860 lb/ft 1.28 kg/m
<a href="#">20022930</a>	1 1/2 in 38.10 mm	1.980 in 50.30 mm	100.000 ft	Red	200.0 psi 1.38 MPa	0.860 lb/ft 1.28 kg/m
<a href="#">20022939</a>	2 in 50.80 mm	2.500 in 63.50 mm	200.000 ft	Red	200.0 psi 1.38 MPa	1.160 lb/ft 1.73 kg/m
<a href="#">20022941</a>	2 in 50.80 mm	2.500 in 63.50 mm	100.000 ft	Red	200.0 psi 1.38 MPa	1.160 lb/ft 1.73 kg/m

[MidEastUS@contitech.us](mailto:MidEastUS@contitech.us)

1-800-235-4632

[Contitech.us](http://Contitech.us)

**ContiTech**