



## TAN FLEXTRA® MH Bulk Transfer Hose



**APPLICATION:** For tank truck and in-plant service. Used to convey nonoily abrasive materials such as sand, limestone, plastic pellets and dry abrasive food products.

**CONSTRUCTION TUBE:** Pureten™ gum rubber (FDA/USDA compliant)

**COVER:** Tan SBR(compound)® gum rubber (corrugated) with yellow spiral stripe (wrapped impression)

**REINFORCEMENT:** Spiral-plied synthetic fabric with wire helix

**TEMPERATURE:** -40 °F to 180 °F (-40 °C to 82 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING (SPIRAL):** Example: Continental Contitech Tan Flextra® with Pureten™ 75 psi WP.

1

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Total Width</u>	<u>Length</u>	<u>Bend Radius</u>	<u>Weight</u>
<a href="#">20019210</a>	1 1/2 in 38.00 mm	2.090 in 53.10 mm	2.090 in 53.10 mm	400.000 ft	4.000 in 102.00 mm	0.990 lb/ft 1.47 kg/m
<a href="#">20019212</a>	2 in 50.80 mm	2.600 in 66.00 mm	2.600 in 66.00 mm	100.000 ft	4.000 in 102.00 mm	1.210 lb/ft 1.80 kg/m
<a href="#">20019216</a>	3 in 76.20 mm	3.630 in 92.20 mm	3.630 in 92.20 mm	100.000 ft	6.000 in 152.00 mm	1.940 lb/ft 2.89 kg/m
<a href="#">20019217</a>	4 in 101.60 mm	4.690 in 119.10 mm	4.690 in 119.10 mm	100.000 ft	9.000 in 229.00 mm	2.740 lb/ft 4.08 kg/m
<a href="#">20019221</a>	5 in 127.00 mm	5.780 in 146.80 mm	5.780 in 146.80 mm	50.000 ft	12.000 in 305.00 mm	4.260 lb/ft 6.34 kg/m
<a href="#">20019223</a>	6 in 152.40 mm	6.780 in 172.20 mm	6.780 in 172.20 mm	50.000 ft	15.000 in 381.00 mm	4.920 lb/ft 7.32 kg/m

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Total Width</u>	<u>Length</u>	<u>Bend Radius</u>	<u>Weight</u>
<a href="#">20019224</a>	6 in 152.40 mm	6.780 in 172.20 mm	6.780 in 172.20 mm	200.000 ft	15.000 in 381.00 mm	4.920 lb/ft 7.32 kg/m
<a href="#">20132671</a>	5 in 127.00 mm	5.780 in 146.80 mm	5.780 in 146.80 mm	400.000 ft	12.000 in 305.00 mm	4.260 lb/ft 6.34 kg/m
<a href="#">20019213</a>	2 1/2 in	3.148 in 79.97 mm	3.148 in	400.000 ft	5.000 in	1.740 lb/ft
<a href="#">20207188</a>	4 in 101.60 mm	4.690 in 119.10 mm	4.690 in 119.10 mm	300.000 ft	9.000 in 229.00 mm	2.740 lb/ft 4.08 kg/m

1

[MidEastUS@contitech.us](mailto:MidEastUS@contitech.us)  
1-800-235-4632  
Contitech.us

**ContiTech**