



WHITE FLEXWING® Food Hose



APPLICATION: A highly flexible hose for gravity flow, pressure, or suction service transferring oily and nonoily edibles from tank truck and in-plant service.

CONSTRUCTION TUBE: White Chemivic™ synthetic rubber (FDA/USDA compliant and conforms to 3-A sanitary standard 18-03)

COVER: White Chemivic synthetic rubber (wrapped impression)

REINFORCEMENT: Spiral-plied synthetic fabric with galvanized wire helix

TEMPERATURE: -25 °F to 230 °F (-32 °C to 110 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendations and coupling procedure.

BRANDING (SPIRAL): Example: Continental Contitech White Flexwing® 150 psi WP; FDA, 3-A, and USDA.

1

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Color</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
20019284	3/4 in 19.10 mm	1.200 in 30.50 mm	100.000 ft	White	150.0 psi 1.03 MPa	0.470 lb/ft 0.70 kg/m
20019286	1 in 25.40 mm	1.440 in 36.60 mm	100.000 ft	White	150.0 psi 1.03 MPa	0.570 lb/ft 0.85 kg/m
20019287	1 1/4 in 31.80 mm	1.700 in 43.20 mm	100.000 ft	White	150.0 psi 1.03 MPa	0.690 lb/ft 1.03 kg/m
20019289	1 1/2 in 38.10 mm	1.970 in 50.00 mm	100.000 ft	White	150.0 psi 1.03 MPa	0.860 lb/ft 1.28 kg/m
20019292	2 in 50.80 mm	2.530 in 64.30 mm	100.000 ft	White	150.0 psi 1.03 MPa	1.230 lb/ft 1.83 kg/m
20019296	2 1/2 in 63.50 mm	3.100 in 78.70 mm	100.000 ft	White	150.0 psi 1.03 MPa	1.810 lb/ft 2.69 kg/m

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Color</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
<u>20019297</u>	3 in 76.20 mm	3.600 in 91.40 mm	100.000 ft	White	150.0 psi 1.03 MPa	2.160 lb/ft 3.21 kg/m
<u>20019301</u>	4 in 101.60 mm	4.640 in 117.90 mm	100.000 ft	White	150.0 psi 1.03 MPa	3.050 lb/ft 4.54 kg/m
<u>20434789</u>	2 in 50.80 mm	2.530 in 64.30 mm	150.000 ft	White	150.0 psi 1.03 MPa	1.230 lb/ft 1.83 kg/m
<u>20477384</u>	1 1/2 in 38.10 mm	1.970 in 50.00 mm	200.000 ft	White	150.0 psi 1.03 MPa	0.860 lb/ft 1.28 kg/m
<u>20480397</u>	1 1/4 in 31.80 mm	1.700 in 43.20 mm	400.000 ft	White	150.0 psi 1.03 MPa	0.690 lb/ft 1.03 kg/m
<u>20494037</u>	1/2 in 38.10 mm	0.950 in 24.10 mm	400.000 ft	White	150.0 psi 1.03 MPa	0.360 lb/ft 0.54 kg/m
<u>20297854</u>	2 in 50.80 mm	2.530 in 64.30 mm	400.000 ft	White	150.0 psi 1.03 MPa	1.230 lb/ft 1.83 kg/m
<u>20297855</u>	3 in 76.20 mm	3.600 in 91.40 mm	400.000 ft	White	150.0 psi 1.03 MPa	2.160 lb/ft 3.21 kg/m
<u>20341074</u>	1 1/2 in 38.10 mm	1.970 in 50.00 mm	400.000 ft	White	150.0 psi 1.03 MPa	0.860 lb/ft 1.28 kg/m