

#### Kuriyama of America, Inc.

360 E. State Parkway

Schaumburg, IL 60173-5335 USA

**Phone:** (847) 755-0360

Toll-Free FAX: (800) 800-0320

International FAX: (847) 885-0996 Email: sales@kuriyama.com

Series Number 2020-600X50, 2020™ Series 6 in. ID and 50 ft Standard Length Heavy Duty Food Grade Polyurethane Fabric Reinforced Material Handling Hose With Grounding Wire

Made in The USA





<u>General Applications | Construction | Service Temperature | Features and Advantages | Nominal Specifications |</u>
Specifications | Note | Caution | Compliance Footnotes

General Applications –

# **General Applications**

- · Bulk truck and railcar unloading
- Food grade material handling heavy duty abrasive
- Material handling heavy duty abrasive
- Suction and discharge

Construction

### Construction

Extra thick double-ply polyurethane tube, polyester fabric reinforcement, rigid PVC helix and grounding wire.

Service Temperature -

Service Temperature [Min]	-40 °C -40 °F
Service Temperature [Max]	65 °C 150 °F

Features and Advantages			-
-------------------------	--	--	---

# versus rubber or PVC hoses.

# • **Food Grade Materials** - Hose Liner (Product Contact Surface) complies with applicable FDA and USDA requirements.

• Extra Thick Abrasion Resistant Double-Ply Polyurethane
Tube - Designed for dry applications where severe abrasion is a
factor. Provides for longer hose life and lower operating costs

- **Fabric Reinforcement** Designed with high tensile strength, food grade, polyester yarn jacket to handle both suction, and higher pressure discharge applications.
- **Grounding Wire** Multi-strand wire helps prevent the buildup of static electricity for added safety and to help keep material flowing smoothly. It's embedded within the rigid helix to prevent contamination of transferred materials.
- **Transparent Construction -** "See-the-flow." Allows for visual confirmation of material flow.
- "Cold-Flex" Materials Hose remains flexible in sub-zero temperatures.
- **Easy Slide Helix** Rigid helix design protects hose tube from cover wear, and allows hose to slide easily over rough surfaces. Easy-to-handle.
- **Oil Resistant Polyurethane Tube** Resists most animal and petroleum based oils.
- Phthalate Free

**Features and Advantages** 

# 

Working Pressure at 68°F	40 psi
Working Pressure at 104°F	22 psi
Vacuum Rating at 68°F	28 inHg
Vacuum Rating at 104°F	25 inHg
Min. Bending Radius at 68°F	16 in
Standard Length	50 ft
Weight	2.86 lbs/ft
Industry Standards/Certifications	BSE/TSE, FDA, EU 2002/95/EC, USDA, RoHS

ecifications	
Brand	Tigerflex®
Туре	Polyurethane Lined Material Handling Hose
Series	2020™
Color	Transparent
Material	Polyurethane
ote	
Note	Service life may vary depending on operating conditions and type of material being conveyed.

Caution

This product is designed to dissipate static electricity when the embedded grounding wire is physically extracted and securely

connected to ground, through the fitting or by other means.

**BSE/TSE** - The majority of the raw materials used in our formulations are not manufactured or derived from materials of animal origin. Nor do our products come into contact with materials of animal origin during processing. Our suppliers of raw materials have assured us their compounds exceed the relevant European Guidance on minimizing the Risk of Transmitting Animal Spongiform Encephalophy Agents Via Human and Veterinary Medical Products.

**FDA -** Material conforms to CFR title 21, parts 177.1680 and 177.2600.

#### **Compliance Footnotes**

**FDA -** Material conforms to CFR title 21, parts 177.2600 and 175.105.

**RoHS** - The product complies with the requirements of the EU directive 2002/95/EC which is on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

**Phthalate Free -** Manufactured from all phthalate free materials.

**USDA** - Hose complies with applicable USDA requirements for use in federally inspected meat and poultry plants.