



Item # 20019235, FLEXTRA DRY MATERIAL MH Bulk Transfer Hose 6 in x 200 ft, 75 psi, Black

APPLICATION: A static dissipating/static conductive hose for tank truck and in-plant service. Used to convey nonoily abrasive materials such as sand, limestone and plastic pellets. Recommended where static buildup can be a problem.

CONSTRUCTION TUBE: 3/16" Gauge Black CHEMITUF(compound)® synthetic rubber (static dissipating/static conductive)

COVER: Black SBR(compound)® synthetic rubber (corrugated) with yellow spiral band (wrapped impression)

REINFORCEMENT: Spiral-plied synthetic fabric with wire helix

TEMPERATURE: -40 °F to 180 °F (-40 °C to 82 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING (SPIRAL): Example: Continental Contitech Flextra® Dry Material 75 psi WP.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Abrasive Materials, Sand, Limestone and Plastic Pellets Transfer
Style	Bulk Transfer Hose
Construction Tube	3/16" Gauge Black Tufsyn® synthetic rubber (static dissipating/static conductive)
Cover	Black Plioflex® synthetic rubber (corrugated) with yellow spiral band (wrapped impression)
Reinforcement	Spiral-plied synthetic fabric with wire helix
Color	BLACK

Min. Temperature	-40 °F -40 °C
Max. Temperature	180 °F 82 °C
Max. Working Pressure	75.0 psi 0.52 MPa
Brands	FLEXTRA® DRY MATERIAL
Order Code	549-126

Specifications

I.D.	6 in 152.40 mm
Nom. O.D.	6.810 in 173.10 mm
Length	50.000 ft
Bend Radius	24.000 in 600.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	5.470 lb/ft 8.15 kg/m

MidEastUS@contitech.us
1-800-235-4632
Contitech.us

ContiTech