



Item # 20459044, EXTREMEFLEX PETROLEUM Transfer Hose 1 1/2 in x 100 ft, 250 PSI, Black

APPLICATION: An extremely flexible and lightweight drop hose for use in tank truck and in-plant operation to transfer diesel, ethanol, gasoline, oil and petroleum base products up to 60% aromatic content. Corrugated construction for lower drag coefficient and superior abrasion resistance.

CONSTRUCTION TUBE: Black Nitrile synthetic rubber (Class A oil resistance)

COVER: Black Chemivic™ synthetic (corrugated)

REINFORCEMENT: Spiral plied synthetic fabric with wire helix

TEMPERATURE: -40 °F to 200 °F (-40 °C to 93 °C)

COUPLINGS: Use Continental Contitech Insta-Lock™ Cam & Groove Fittings.

BRANDING (SPIRAL): Example: Plicord® ExtremeFlex™ Petroleum Transfer



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Petroleum Transfer
Style	Petrol Transfer Hose
Construction Tube	Black Nitrile synthetic rubber (Class A oil resistance)
Cover	Black Chemivic™ synthetic (corrugated)
Reinforcement	Spiral plied synthetic fabric with wire helix
Color	Black

Min. Temperature	-40 °F -40 °C
Max. Temperature	200 °F 93 °C
Max. Working Pressure	250.0 psi 1.72 MPa
Brand	PLICORD® EXTREMEFLEX™
Order Code	543-216

Specifications

I.D.	1 1/2 in 38.00 mm
Nom. O.D.	1.910 in 48.50 mm
Length	100.000 ft
Bend Radius	1.500 in 38.10 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	0.730 lb/ft 1.08 kg/m

MideastUS@contitech.us
1-800-235-4632
Contitech.us

ContiTech