



Item # 20021670, REDWING Fuel Oil Dispensing Hose 1 in x 175 ft, 250 PSI, Red

APPLICATION: Redwing® Fuel Oil is for transfer and delivery of fuel oil and petroleum products for home delivery, commercial and industrial service. Redwing Fuel Oil has two textile braids. The braided construction reduces kinking and twisting when reeling. The smooth cover has low drag resistance.

CONSTRUCTION TUBE: Nitrile synthetic rubber (ORS)

COVER: Red Chemivic[™] synthetic rubber (smooth finish) (ORS)

REINFORCEMENT: Braided (2) synthetic yarn

TEMPERATURE: -40 °F to 140 °F (-40 °C to 60 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: 1" (25.4 mm) 2 BD Redwing® Fuel Oil Continental Contitech. Made in USA.



Product Specifications | Specifications

Type Oil Transfer Style Redwing Fuel Oil Dispense Hose Construction Tube Nitrile synthetic rubber (ORS) Cover Red Chemivic™ synthetic rubber (smooth finish) (ORS) Reinforcement Braided (2) synthetic yarn Color RED

Min. Temperature	-40 °F -40 °C
Max. Temperature	140 °F 60 °C
Max. Working Pressure	250.0 psi 1.72 MPa
Brands	REDWING®
Order Code	532-016

	Specifications	-
I.D.	1 in 25.40 mm	
Nom. O.D.	1.500 in 38.10 mm	
Length	175.000 ft	
Weight	0.570 lb/ft 0.85 kg/m	
Weight	0.6470 lb	

MideastUS@contitech.uss 1-800-235-4632 Contitech.us ContiTech