



Item # 20021750, REDWING Fuel Oil Dispensing Hose MMOT 1 in x 1 ft, 250 PSI, Red

APPLICATION: Redwing® Fuel Oil is for transfer and delivery of fuel oil and petroleum products for home delivery, commercial and industrial service. Redwing Fuel Oil has two textile braids. The braided construction reduces kinking and twisting when reeling. The smooth cover has low drag resistance.

CONSTRUCTION TUBE: Nitrile synthetic rubber (ORS)

COVER: Red Chemivic™ synthetic rubber (smooth finish) (ORS)

REINFORCEMENT: Braided (2) synthetic yarn

TEMPERATURE: -40 °F to 140 °F (-40 °C to 60 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: 1" (25.4 mm) 2 BD Redwing® Fuel Oil Continental Contitech. Made in USA.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Oil Transfer
Style	Redwing Fuel Oil Dispense Hose
Construction Tube	Nitrile synthetic rubber (ORS)
Cover	Red Chemivic™ synthetic rubber (smooth finish) (ORS)
Reinforcement	Braided (2) synthetic yarn
Color	RED

Min. Temperature	-40 °F -40 °C
Max. Temperature	140 °F 60 °C
Max. Working Pressure	250.0 psi 1.72 MPa
Brands	REDWING®
Order Code	532-016

Specifications

I.D.	1 in 25.40 mm
Nom. O.D.	1.500 in 38.10 mm
Length	1.000 ft
Weight	0.570 lb/ft 0.85 kg/m
Weight	64.078 lb

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech