



Item # 20021736, REDWING Fuel Oil Dispensing Hose 1 1/2 in x 125 ft, 250 PSI, Red

APPLICATION: Redwing® Fuel Oil is for transfer and delivery of fuel oil and petroleum products for home delivery, commercial and industrial service. Redwing Fuel Oil has two textile braids. The braided construction reduces kinking and twisting when reeling. The smooth cover has low drag resistance.

CONSTRUCTION TUBE: Nitrile synthetic rubber (ORS)

COVER: Red Chemivic™ synthetic rubber (smooth finish) (ORS)

REINFORCEMENT: Braided (2) synthetic yarn

TEMPERATURE: -40 °F to 140 °F (-40 °C to 60 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: 1" (25.4 mm) 2 BD Redwing® Fuel Oil Continental Contitech. Made in USA.



[Product Specifications](#) | [Specifications](#)

Product Specifications

| | |
|--------------------------|--|
| Type | Oil Transfer |
| Style | Redwing Fuel Oil Dispense Hose |
| Construction Tube | Nitrile synthetic rubber (ORS) |
| Cover | Red Chemivic™ synthetic rubber (smooth finish) (ORS) |
| Reinforcement | Braided (2) synthetic yarn |
| Color | RED |

| | |
|------------------------------|-----------------------|
| Min. Temperature | -40 °F -40 °C |
| Max. Temperature | 140 °F 60 °C |
| Max. Working Pressure | 250.0 psi 1.72 MPa |
| Brands | REDWING® |
| Order Code | 532-016 |

Specifications

| | |
|------------------|--------------------------|
| I.D. | 1 1/2 in 38.10 mm |
| Nom. O.D. | 2.100 in 53.30 mm |
| Length | 125.000 ft |
| Weight | 0.920 lb/ft 1.37 kg/m |
| Weight | 1.0480 lb |

MideastUS@contitech.us
1-800-235-4632
Contitech.us

ContiTech