



## Item # 20339606, FLEXWING VERSAFUEL Petroleum Transfer Hose 1 in x 100 ft, 150 PSI, Black

**APPLICATION:** For use in tank truck and in-plant operation to transfer diesel, biodiesel blends, B-100, ethanol blends, gasoline, oil and petroleum base products up to 60% aromatic content.

**CONSTRUCTION TUBE:** Synthetic rubber (static dissipating).

**COVER:** Black synthetic rubber with excellent resistance to biodiesel, ethanol, oil/petroleum products and abrasion.

**REINFORCEMENT:** Spiral-plied synthetic fabric with helix wire.

**TEMPERATURE:** -30 °F to 180 °F (-34 °C to 82 °C)

**COUPLINGS:** Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product.

**BRANDING (SPIRAL):** Example: Continental Contitech Flexwing VersaFuel™ 150 psi WP.



[Product Specifications](#) | [Specifications](#)

### Product Specifications

<b>Type</b>	Petroleum Transfer
<b>Style</b>	Petrol Transfer Hose
<b>Construction Tube</b>	Synthetic rubber (static dissipating).
<b>Cover</b>	Black synthetic rubber with excellent resistance to biodiesel, ethanol, oil/petroleum products and abrasion.
<b>Reinforcement</b>	Spiral-plied synthetic fabric with helix wire.

<b>Color</b>	Black
<b>Min. Temperature</b>	-30 °F -34 °C
<b>Max. Temperature</b>	180 °F 82 °C
<b>Max. Working Pressure</b>	150.0 psi 1.03 MPa
<b>Brand</b>	FLEXWING VERSAFUEL™
<b>Order Code</b>	543-422

### Specifications

<b>I.D.</b>	1 in 25.40 mm
<b>Nom. O.D.</b>	1.500 in 38.10 mm
<b>Length</b>	100.000 ft
<b>Bend Radius</b>	2.000 in 50.00 mm
<b>Vacuum Rating</b>	29.000 inHg 737.00 mmHg
<b>Weight</b>	0.590 lb/ft 0.88 kg/m

[MideastUS@contitech.us](mailto:MideastUS@contitech.us)

1-800-235-4632

Contitech.us

**ContiTech**