



Item # 20339628, FLEXWING VERSAFUEL Petroleum Transfer Hose 2 in x 100 ft, 150 PSI, Black

APPLICATION: For use in tank truck and in-plant operation to transfer diesel, biodiesel blends, B-100, ethanol blends, gasoline, oil and petroleum base products up to 60% aromatic content.

CONSTRUCTION TUBE: Synthetic rubber (static dissipating).

COVER: Black synthetic rubber with excellent resistance to biodiesel, ethanol, oil/petroleum products and abrasion.

REINFORCEMENT: Spiral-plied synthetic fabric with helix wire.

TEMPERATURE: -30 °F to 180 °F (-34 °C to 82 °C)

COUPLINGS: Use Continental Contitech Insta-Lock Cam & Groove Fittings with this product.

BRANDING (SPIRAL): Example: Continental Contitech Flexwing VersaFuel™ 150 psi WP.



[Product Specifications](#) | [Specifications](#)

Product Specifications

Type	Petroleum Transfer
Style	Petrol Transfer Hose
Construction Tube	Synthetic rubber (static dissipating).
Cover	Black synthetic rubber with excellent resistance to biodiesel, ethanol, oil/petroleum products and abrasion.
Reinforcement	Spiral-plied synthetic fabric with helix wire.

Color	Black
Min. Temperature	-30 °F -34 °C
Max. Temperature	180 °F 82 °C
Max. Working Pressure	150.0 psi 1.03 MPa
Brand	FLEXWING VERSAFUEL™
Order Code	543-422

Specifications

I.D.	2 in 51.20 mm
Nom. O.D.	2.550 in 64.90 mm
Length	100.000 ft
Bend Radius	5.000 in 125.00 mm
Vacuum Rating	29.000 inHg 737.00 mmHg
Weight	1.210 lb/ft 1.80 kg/m

MideastUS@contitech.us

1-800-235-4632

Contitech.us

ContiTech